

VIDVIE PRODUCT CATALOG

VIDVIE

<https://vidvietech.com/>

Foshan
Office: D1-03, Building D, Nanhai New Economic Industry Center,
No. 1 Xianan Road, Guicheng Street, Nanhai District, Foshan City, Guangdong

Shop NO.1 : No. 127, the 1st floor, Guangzhou the thirteen-hongs Culture and Technology Center, Exhibition
Building on the right side of New Asia, No. 37 Xidi Erma Road, Liwan District, Guangzhou

Shenzhen
RmY2-5F-03, No.5 Creative Zone, Yayuan Road, Bantian Street, Longgang District, Shenzhen, China

Shop NO.2 : A46-47, 1/F, Yale Smart Wearable International Market, Block D, Electronic & Technology Building,
Huaqiang North, Shenzhen

Contact Us:

✉ business@vidvietech.com

☎ +86 18565066884

🗣 Rain-VIDVIE

Super Design. Top Life >>>

CHARGER



BRITISH PLUG CHARGER




PLB118
 Input: AC 100V-240V~50/60Hz 0.3A
 Output: 5V / 2.4A
 Size: 60 X 48 X 54mm
 Ports: 2 X USB
 Working Temperature: -10°C - 50°C
12W



PLB119
 Input: AC 100V-240V~50/60Hz 0.3A
 Output: 5V / 2.4A
 Size: 47 X 26 X 78mm
 Ports: 2 X USB
 Working Temperature: -10°C - 50°C
12W



PLB133
 Input: AC 100V-240V~50/60Hz 0.3A
 Output: 5V / 2.4A
 Size: 79 X 50 X 48mm
 Ports: 2 X USB
 Working Temperature: -10°C - 50°C
12W



PLB131
 Input: AC 100V-240V~50/60Hz 0.5A
 Output: 5V / 4.8A
 Size: 81 X 48 X 30.5mm
 Ports: 3 X USB
 Working Temperature: -10°C - 50°C
4.8A





PLB140

Input: AC 100~240V, 50/60Hz 0.3A
Output: DC 5V / 2.4A (MAX)
Size: 45 X 73.5 X 40mm
Ports: 2 X USB
Working Temperature: -10°C - 50°C

12W



67W
GaN

22.5W
USB-A



PLB142

Input: AC 100V~240V~50/60Hz, 1.5A(Max)
Output: USB-C1/C2: 5V≡3A, 9V≡3A, 12V≡3A, 15V≡3A, 20V≡3.35A, 67W(Max)
USB-A: 4.5V≡5A, 5V≡4.5A, 9V≡2A, 12V≡1.5A 22.5W(MAX)
USB-C1+USB-C2: 45W+20W 65W(Max)
USB-C1+USB-A: 45W+18W 63W(Max)
USB-C2+USB-A: 5V≡3.6A 18W(Max)
USB-C1+USB-C2+USB-A: 45W+18W 63W(Max)
PPS: 3.3~20.3V/3.3A Size: 31.8 X 84 X 37mm Ports: 3 X USB
Working Temperature: 0°C - 40°C



33W
GaN



PLB141C

Input: 100V~240V~50/60Hz 0.8A Max
Output: USB-C 5V/3A, 9V/3A, 12V/2.5A, 15V/2A, 20V/1.5A
PPS: 3.3V~11V/3A 33W Max
Size: 48.9 X 68.5 X 43.4mm
Port: 1 X USB
Working Temperature: -10°C - 50°C

33W



40W
GaN



PLB146

Input: AC 100V~240V~50/60Hz, 1.2A(Max)
Output: USB-C1: 5V≡3A, 9V≡3A, 12V≡3A, 15V≡2.5A, 20V≡2A 40W(Max) PPS: 3.3V~11V 3A
USB-C2: 5V≡3A, 9V≡3A, 12V≡3A, 15V≡2.5A, 20V≡2A 40W(Max) PPS: 3.3V~11V≡3A
USB-C1+USB-C2 total output:
PD 25W+PD 15W or PD 35W+5W or PD 20W+PD 20W
Size: 48.7 X 44 X 69.7 mm Ports: 2 X USB
Working Temperature: 0°C - 40°C

40W



33W

QC 4.0



PLB137C-Q

Input: AC 100~240V, 0.8A Max
USB-A output: DC 5V/4A, 9V/3A, 12V/2.5A
Type-C output: DC 5V/3A, 9V/3A, 12V/2.5A, 15V/2A, 20/1.5A
PPS: DC 11V/3A 33W Max
USB-A+Type-C output: 5V/3A
Size: 82.2*44.6*48mm
Ports: 2 X USB
Working Temperature: 0°C - 40°C

PD 33W QC 4.0



20W



PLB143

Input: AC 110~230V 50/60Hz 0.5A
USB-A output: DC 5V/3A, 9V/2A, 12V/1.5A (18W)
Type-C output: DC 5V/3A, 9V/2.22A, 12V/1.67A (20W)
USB-A+Type-C output: DC 5V/3A (15W)
Ports: 2-USB Product size: 43.8*28.4*73mm
Product weight: 45.3g
Working temperature: -10°C - 50°C

PD 20W





UK PLB147

Input: 100-240V~50/60Hz, 2.5A Max.
Output: USB-C1: 5V≡3A, 9V≡3A, 12V≡3A, 15V≡3A, 20V≡5A, 100W(Max) USB-C2: 5V≡3A, 9V≡3A, 12V≡3A, 15V≡3A, 20V≡5A, 100W(Max) PPS:3.3-11V≡3A
USB-A1: 4.5V≡5A, 5V≡4.5A, 5V≡3A, 9V≡2A, 12V≡1.5A, 22.5W(Max) USB-A2: 4.5V≡5A, 5V≡4.5A, 5V≡3A, 9V≡2A, 12V≡1.5A, 22.5W(Max) USB-C1+USB-C2: 65W+30W 95W(Max) USB-C1+USB-A1: 65W+18W 83W(Max) USB-C1+USB-A2: 65W+18W 83W(Max) USB-C2+USB-A1: 65W+18W 83W(Max) USB-C2+USB-A2: 65W+18W 83W(Max) USB-A1+USB-A2: 22.5W(Max) USB-C1+USB-C2+USB-A1: 45W+30W+18W 93W(Max) USB-C1+USB-C2+USB-A2: 45W+30W+18W 93W(Max) USB-C1+(USB-A1+USB-A2): 65W+22.5W 87.5W(Max) USB-C2+(USB-A1+USB-A2): 65W+22.5W 87.5W(Max) USB-C1+USB-C2+(USB-A1+USB-A2): 45W+30W+22.5W 97.5W (Max) Ports: 4-USB
Product size: 85*85*26.3mm Product weight: 277g
Working temperature:-10 °C-50 °C

PLB147



UK PLB144

Input: AC 110-230V 50/60Hz 0.3A
Output: DC 5V/2.4A (MAX)
Port: 1-USB Product size: 43.8*28.4*73mm
Product weight: 37.6g
Working temperature: -10 °C-50 °C

12W



UK PLB145

Input: AC 110-230V 50/60Hz 0.3A
Output: DC 5V/2.4A (MAX)
Ports: 2-USB Product size: 43.8*28.4*73mm
Product weight: 38.7g
Working temperature: -10 °C-50 °C

12W



UK PLB148

Input: AC 100-240V, AC 50/60Hz
USB-A output: DC 5V≡3A, 9V≡2.22A, 12V≡1.67A
Type-C output: DC 5V≡3A, 9V≡2.22A, 12V≡1.67A
USB-A+Type-C output: DC 5V≡3A
Ports: 2-USB
Product size: 49*74*38.7mm
Product weight: 45.3g
Working temperature: -10°C - 70°C

20W



UK PLB149

Input: AC 100-240V, AC 50/60Hz
Output: QC 3.0 5V≡3A, 9V≡2A, 12V≡1.5A
Port: 1-USB
Product size: 49*74*38.7mm
Product weight: 41.16g
Working temperature: -10°C - 70°C

QC 3.0



UK PLB150

Input: AC 100-240V, AC 50/60Hz
Output: DC 5V 2.4A
Ports: 2-USB
Product size: 49*74*38.7mm
Product weight: 37.5g
Working temperature: -10°C - 70°C

12W





PLB153

67W
GaN



PLB151

Input: AC 100V-240V~50/60Hz, 1.5A(Max)
Output: USB-C1: 5V=3A, 9V=3A, 12V=3A, 15V=3A, 20V=3.35A (67W Max)
USB-C2: 5V=3A, 9V=3A, 12V=3A, 15V=3A, 20V=3.35A (67W Max)
PPS: 3.3V~11V/4.5A USB-C1+USB-C2: PD45W+PD20W
USB-C1+USB-C2: 67W Max. Ports: 2-USB
Product size: 44*73*39mm Product weight: 115.3g
Color: White Working temperature: 0°C~40°C

67W



New

20W
PD



PLB153

Input: AC 100-240V~50/60Hz 0.8A(Max)
Output: DC 5V=3A, 9V=2.22A, 12V=1.67A 20W
Port: 1X Type-C
Product size: 48*43*64mm
Product weight: 48.3g
Working temperature: 0°C~40°C

20W



New

PD
33W



PLB154

Input: AC 100-240V~50/60Hz 0.8A(Max)
Output: 5V=3A, 9V=3A, 12V=2.5A, 15V=2A, 20V=1.5A
Port: 1X Type-C PPS: 3.3V~11V 3A 33W Max
Product size: 48*43*64mm
Product weight: 53.8g
Working temperature: 0°C~40°C

33W



New

PD
33W

USB
30W



PLB155

Input: AC 100-240V~50/60Hz 0.8A(Max)
Output: 5V=3A, 9V=3A, 12V=2.5A, 15V=2A, 20V=1.5A
USB Output: 5V=3A, 9V=3A, 12V=2.5A, 15V=2A, 20V=1.5A
Port: Type-C+USB PPS: 3.3V~11V 3A 33W Max
Product size: 48*43*64mm
Product weight: 51.1g
Working temperature: 0°C~40°C

33W



New

PD
20W



PLB156

Input: AC 100-240V~50/60Hz 0.8A Max
Output: 5V=3A, 9V=2.22A, 12V=1.67A, 20V=1.5A
Total power: 20W Max Interface: Type-C
Product size: 48*43*64mm
Product weight: 53.8g
Working temperature: 0°C~40°C

20W



New

PD
33W



PLB157

Input: AC 100-240V~50/60Hz 0.8A Max
Output: 5V=3A, 9V=3A, 12V=2.5A, 15V=2A, 20V=1.5A
PPS: 3.3V~11V=3A 33W Max Total power: 33W Max
Interface: Type-C Product size: 48*43*64mm
Product weight: 53.8g
Working temperature: 0°C~40°C

33W



New

PD
33W

USB
30W



PLB158

Input: 100-240V~50/60Hz 0.8A Max
Type-C Output: 5V=3A, 9V=3A, 12V=2.5A, 15V=2A, 20V=1.5A PPS: 3.3V~11V 3A 33W Max
USB Output: 5V=3A, 9V=3A, 12V=2.5A, 15V=2A, 20V=1.5A Total power: 33W Max
Interface: Type-C Product size: 48*43*64mm
Product weight: 53.8g
Working temperature: 0°C~40°C

33W





UK PLB159

Input: 100-240V~50/60Hz 1.5A Max.
 USB-C1 output: 5V=3A, 9V=3A,
 12V=3A, 15V=3A, 20V=3.5A (70W)
 USB-C2 output: 5V=3A, 9V=3A,
 12V=3A, 15V=3A, 20V=3.5A (70W)
 USB-A1 output: 5V=3A, 9V=3A,
 12V=2.5A, 15V=2A, 20V=1.5A (30W)
 USB-A2 output: 5V=3A, 9V=3A,
 12V=2.5A, 15V=2A, 20V=1.5A (30W)
 Total output: 47W+5V=3.1A
 Size: 85*85*27mm
 Product weight: 134.5g
 Operating temperature: -10°C-50°C

PLB159



PLB161

New

PD 33W



UK PLB160

Input: AC 100-240V 50/60Hz 0.5A
 Type-C1 output: DC 5V=3A, 9V=3A, 12V=2.5A(30W)
 PPS: 3.3-11V=3A 33W
 Type-C2 output: DC 5V=3A, 9V=3A, 12V=2.5A(30W)
 PPS: 3.3-11V=3A 33W
 Type-C1+Type-C2 output: DC 5V=3A (15W)
 Product size: 49.4*43.2*72mm Product weight: 59.3g
 Working temperature: 0°C - 40°C

33W



New

PD 45W



UK PLB161

Input: AC 100-240V 50/60Hz 0.5A
 Type-C1 output: DC 5V=3A, 9V=3A, 12V=3A, 15V=3A,
 20V=2.25A (45W) PPS: 3.3-11V=3A 33W
 Type-C2 output: DC 5V=3A, 9V=3A, 12V=3A, 15V=3A,
 20V=2.25A (45W) PPS: 3.3-11V=3A 33W
 Type-C1+Type-C2 output: 25W+20W
 Product size: 49.4*47.5*77mm Product weight: 81.7g
 Working temperature: 0°C - 40°C

45W



New

MAX 65W

USB 22.5W



UK PLB162

Input: 110-240V~50/60Hz 1.5A Max
 Type-C1/Type-C2 output: DC 5V=3A, 9V=3A,
 12V=3A, 15V=3A, 20V=3.25A(65W Max)
 USB output: DC 5V=3A, 9V=2.5A, 12V=1.87A(22.5W Max)
 Type-C1+Type-C2 output: 45W+20W(65W Max)
 Type-C1+USB output: 45W+18W(63W Max)
 Type-C2+USB output: DC 5V=2.4A+DC 5V=2.4A(24W Max)
 Type-C1+Type-C2+USB output: 45W+10W+10W(65W Max)
 Product size: 56.3*49*89mm Product weight: 130g
 Working temperature: 0°C - 40°C

65W





PLM361



TA4404

New

PD
33W



UK PLM360

Input: AC 100-240V 50/60Hz 0.5A
Type-C1 output: DC 5V=3A, 9V=3A, 12V=2.5A(30W)
PPS: 3.3-11V=3A 33W
Type-C2 output: DC 5V=3A, 9V=3A, 12V=2.5A(30W)
PPS: 3.3-11V=3A 33W
Type-C1+Type-C2 output: DC 5V=3A (15W)
Product size: 30.6*43.2*58.7mm Product weight: 52g
Working temperature: 0°C - 40°C

33W



New

PD
45W



UK PLM361

Input: AC 100-240V 50/60Hz 0.5A
Type-C1 output: DC 5V=3A, 9V=3A, 12V=3A, 15V=3A, 20V=2.25A (45W) PPS: 3.3-11V=3A 33W
Type-C2 output: DC 5V=3A, 9V=3A, 12V=3A, 15V=3A, 20V=2.25A (45W) PPS: 3.3-11V=3A 33W
Type-C1+Type-C2 output: 25W+20W
Product size: 47.5*30.7*63.7mm Product weight: 81.4g
Working temperature: 0°C - 40°C

45W



New

MAX
65W

USB
22.5W



UK PLM362

Input: 110-240V~50/60Hz 1.5A Max
Type-C1/Type-C2 output: DC 5V=3A, 9V=3A, 12V=3A, 15V=3A, 20V=3.25A(65W Max)
USB output: DC 5V=3A, 9V=2.5A, 12V=1.87A(22.5W Max)
Type-C1+Type-C2 output: 45W+20W(65W Max)
Type-C1+USB output: 45W+18W(63W Max)
Type-C2+USB output: DC 5V=2.4A+DC 5V=2.4A(24W Max)
Type-C1+Type-C2+USB output: 45W+10W+10W(65W Max)
Product size: 56.3*29*75mm Product weight: 117.8g
Working temperature: 0°C - 40°C

65W



New

MAX
2.4A



TA4403

Material: ABS+PC
Rating: 100-250V 10A Max, 2500W
Maxinput: 100-250V 50-60Hz 0.5A
USB output: 5.0V-.2.4A
USB-A+USB-C output: 2.4A 12W Max
Rating: 10A MAX. Size: 70*47*53.5mm
Weight: 134.7g Working temperature: -10-45°C

2.4A



New

PD
20W



TA4404

Material: ABS+PC
Type-C output: 5V=3A, 9V=2.22A, 12V=1.67A 20W MAX
USB output: 5V=3A, 9V=2A, 12V=1.5A 18W MAX
Type-C+USB total output: 5V 3A MAX
Fuse rating: 8A MAX
Maximum power: 880W at 110V/1840W at 230V
Product size: 68.42*54.78*52.65mm
Product weight: 136.68g
Colour: Black Working temperature: 0°C - 40°C

20W





TA4405



TA4407

New

OUT
25W



TA4405

USB Input: 100-240V~50/60Hz 0.8A
Type-C output: 3.3-11V=2.25A(PPS) 5V=3A, 9V=2.77A, 12V=2.08A(25W) USB output: 5V=3A, 9V=2.22A, 12V=1.67A(20W)
Type-C+USB output: 15W Max Product size: 42*70*25.4mm
Product weight: 64.5g
Working temperature: 0°C - 40°C

20W 25W



New

OUT
65W



TA4407

Type-C1 output: 3.3-11V 3A, 5V/9V/12V/15V=3A, 20V=3.25A (65W Max) Type-C2 output: 3.3-11V=3A, 5V/9V/12V/15V=3A, 20V=3.25A (65W Max)
USB output: 4.5V=5A, 5V=4.5A, 9V=3A, 12V=2.5A, 20V=1.5A (30W Max)
Type-C1+Type-C2 output: 45W+18W (63W Max)
Type-C1+Type-C2+USB output: 45W+5V 3A (60W Max)
Total output: 65W Max Product size: 54*78*52.3mm
Product weight: 195.1g Working temperature: 0°C - 40°C

65W



New

OUT
33W



TA4406

Input: 100-240V~50/60Hz 0.8A
Type-C output: 5V=3A, 9V=3A, 12V=2.5A, 15V=2A, 20V=1.5A(30W)
PPS: 5.5-11V=3A 33W Product size: 42*70*25.4mm
Product weight: 64g
Operating temperature: 0°C - 40°C

33W



New

OUT
100W




TA4408

Type-C1/C2/C3 out: 3.3-21V=5A(PPS)
Type-C1/C2/C3 output: 5V/9V/12V/15V=3A, 20V=5A (100W) USB output: 5V/9V/12V/20V=3A (60W)
Type-C1+C2+(C3+USB) output: 65W+20W+15W
Type-C1+C2+C3 output: 60W+20W+20W
Type-C1+USB / C2+USB output: 70W+30W
Type-C1+(C3+USB) / C2+(C3+USB) output: 80W+15W
Type-C3+USB output: 15W Max Product size: 55*100*53mm
Product weight: 297.2g Working temperature: 0°C - 40°C

100W



CHARGER



BRITISH PLUG CHARGER



XL-PLB118

Material: PC flame retardant
Input: AC 100V~240V~50/60Hz 0.7A
Output: USB-A: 5V / 3A, 9V / 2A, 12V / 1.5A (QC 18W)
TYPE-C: 5V / 3A, 9V / 2.25A, 12V / 1.6A (PD 20W MAX)
Size: 75 X 40.2 X 49.7mm Ports: 2 X USB
Color: Black

20W



XL-PLB119

Material: ABS+PC flame retardant
Input: AC 100V~240V~50/60Hz 0.3A
Output: 5V / 2.4A
Size: 75 X 40.2 X 49.7mm
Ports: 2 X USB
Color: Black

12W



XL-PLB122

Input: 100~240V~50/60Hz 1.5A Max
Output: Type-C1/C2: 5V=3A, 9V=3A, 12V=3A, 15V=3A, 20V=3.5A
PPS: 3.3V~11V=5A USB1/2: 5V=3A, 9V=3A, 12V=2.5A, 15V=2A,
20V=1.5A Type-C1+C2: 45W(PPS: 3.3V~11V=4.05A)+20W
Type-C1+USB1/2: 45W+18W Type-C2+USB1/2: 5V=3.6A 18W
USB1+USB2: 5V=3.6A 18W Type-C1+Type-C2+USB1+USB2:
45W+5V=3.6A 18W Size: 48.5*92*43mm Product weight: 151.6g
Operating temperature: -10°C~50°C

70W



XL-PLB123

Input: 100~240V~50/60Hz 1.5A Max
Output: Type-C1/C2: 5V=3A, 9V=3A, 12V=3A, 15V=3A, 20V=3.5A
PPS: 3.3V~11V=5A USB1/2: 5V=3A, 9V=3A, 12V=2.5A, 15V=2A,
20V=1.5A Type-C1+C2: 45W(PPS: 3.3V~11V=4.05A)+20W
Type-C1+USB1/2: 45W+18W Type-C2+USB1/2: 5V=3.6A 18W
USB1+USB2: 5V=3.6A 18W Type-C1+Type-C2+USB1+USB2:
45W+5V=3.6A 18W Size: 42*69*35mm Product weight: 215g
Operating temperature: -10°C~50°C

70W



VIDVIE

<https://vidvietech.com/>

Foshan
Office: D1-03, Building D, Nanhai New Economic Industry Center,
No. 1 Xianan Road, Guicheng Street, Nanhai District, Foshan City, Guangdong

Shop NO.1 : No. 127, the 1st floor, Guangzhou the thirteen-hongs Culture and Technology Center, Exhibition
Building on the right side of New Asia, No. 37 Xidi Erma Road, Liwan District, Guangzhou

Shenzhen
RmY2-5F-03, No.5 Creative Zone, Yayuan Road, Bantian Street, Longgang District, Shenzhen, China

Shop NO.2 : A46-47, 1/F, Yale Smart Wearable International Market, Block D, Electronic & Technology Building,
Huaqiang North, Shenzhen

Contact Us:

✉ business@vidvietech.com

☎ +86 18565066884

☎ Rain-VIDVIE



VIDVIE® is a registered trademark, owned by Shenzhen Aifeng Chengpin Trading Co., Ltd. Shenzhen Aifeng Chengpin Trading Co., Ltd. has all the right to interpret matters related to this album.
The products displayed in the VIDVIE full-category product catalog are new products as of January 2021. New products on the shelves after January 2021 are not in this catalog. You can consult our sales staff for the latest product information.
If the products shown in this album are revised in the future, please refer to the information provided by the salesperson of our company. This album is for reference only.