

VIDVIE PRODUCT CATALOG

VIDVIE

<https://vidvietech.com/>

Foshan
Office: D1-03, Building D, Nanhai New Economic Industry Center,
No. 1 Xianan Road, Guicheng Street, Nanhai District, Foshan City, Guangdong

Shop NO.1 : No. 127, the 1st floor, Guangzhou the thirteen-hongs Culture and Technology Center, Exhibition
Building on the right side of New Asia, No. 37 Xidi Erma Road, Liwan District, Guangzhou

Shenzhen
RmY2-5F-03, No.5 Creative Zone, Yayuan Road, Bantian Street, Longgang District, Shenzhen, China

Shop NO.2 : A46-47, 1/F, Yale Smart Wearable International Market, Block D, Electronic & Technology Building,
Huaqiang North, Shenzhen

Contact Us:

✉ business@vidvietech.com

☎ +86 18565066884

🌐 Rain-VIDVIE

Super Design. Top Life >>>

CAR CHARGER



CC521C

CC517

CB518C



CC509

Material: ABS
Function: Dual USB output, multiple circuit protection
USB PORT: 2 X USB
Input: 12-24V
Output: 5V / 2.1A
Size: 74 X 40 X 23mm
Color: White



CC517

Material: Aluminum Alloy+PC
Function: Dual USB output, multiple circuit protection
USB PORT: 2 X USB
Input: 12-24V
Output: 5V / 2.4A
Size: 63 X 28 X 28mm
Color: Grey



CC517C

Material: Aluminum Alloy+PC
Protocol: PD2.0, QC3.0, QC2.0, FCP, AFC
USB PORT: 2 X USB Input: 12-24V
Output: UCB-C: 5V / 3A, 9V / 2.25A, 12 / V1.6A, (PD 20W MAX)
UCB-A: 5V / 3A, 9V / 2A, 12 / V1.5A, (QC 18W MAX)
Size: 63 X 28 X 28mm
Color: Grey



CC518

Material: PC flame retardant
Function: Dual USB output, multiple circuit protection
USB PORT: 2 X USB
Input: 12-24V
Output: 5V / 2.4A
Size: 64 X 31 X 31mm
Color: Black



CC518C

Material: PC flame retardant
Protocol: PD2.0, QC3.0, QC2.0, FCP, AFC
USB PORT: 2 X USB Input: 12-24V
Output: UCB-C: 5V / 3A, 9V / 2.25A, 12 / V1.6A, (PD 20W MAX)
UCB-A: 5V / 3A, 9V / 2A, 12 / V1.5A, (QC 18W MAX)
Total output: 5V / 3.1A smart balance shunt
Size: 64 X 31 X 31mm Color: Black



Material: Aluminum alloy + ABS
Protocol: supporting PD2.0/PD3.0/PPS; QC2.0/QC3.0/
AFC/FCP/SCP and other mainstream fast charging protocols
Input: 12-24V
USB output: DC 4.5V/5A, 5V/4.5A,
5V/3.6A, 9V/2.5A, 12V/2.25A (27W Max)
Type-C output: DC 5V/3.6A, 9V/3A,
12V/2.25A, 20V/2.25A (45W Max)
Size: 33 X 33 X 73mm Weight: 43g
Color: Translucent gray



Material: Aluminum alloy
Protocol: PD20W is really fast charging,
supports all Apple mobile phones, supports PD20W,
QC3.0/QC2.0, AFC, PPS and other charging protocols
Input: 12-24V
USB output: DC 5V/3A, 9V/2A, 12V/1.5A(18W Max)
Type-C output: DC 5V/3A, 9V/2.22A, 12V/1.67A(20W Max)
Size: 24 X 20.5 X 38.5mm Weight: 22.75g
Color: Metal Grey



Material: PC+Aluminum Alloy
USB port: QC2.0/QC3.0/AFC/FCP/SCP/SFCP/
BC12/Apple/MTK PE+11/MTK PE+2.0
Type-C port: PD2.0/PD3.0/PPS/QC2.0/QC3.0/AFC/FCP/SCP
Input: DC12~24V USB-A output: 4.5V/5A, 5V/4.5A, 5V/3.6A,
9V/2.5A, 12V/2A (24W Max) Type-C output: 5V/3.6A, 9V/3A,
12V/2.25A, 20V/2.25A (45W Max) USB-A + Type-C output:
5V/4.8A Product size: 97mm*61mm*33mm Product weight: 53g
Color: Black + Space gray The total output power of the
expansion port: ≤80W (does not support the cigarette
lighting function)



Material: Aluminum alloy
Protocol: Support PD3.0, PD2.0, QC3.0/QC2.0, FCP, SCP, AFC, PPS and other charging protocols.
Input: 12~24V USB output: 5V/3A, 9V/3A, 12V/ 2.5A(30W Max)
Type-C output: 5V/3A, 9V/3A, 12V/2.5A, 15V/2A, 20V/1.5A(30W Max)
PPS: 11V/3A (33W Max)
Size: 23.5*44*23.5mm Weight: 28.3g
Color: Metal Grey



Input : DC 12-24V
Output : DC 5V / 2.4A
Ports: 2-USB
Size : 25 * 57 * 25mm
Weight: 19g
Color: Grey



Material: Plastic+PC
Input: DC 12-24V
USB1 output: 4.5V 5A, 5V 4.5A, 5V 3.6A, 9V 2.5A, 12V 2.25A(27W Max)
USB2 output: 5V 3.4A, 9V 2A, 12V 1.5A(18W Max)
USB3 output: 4.5V 5A, 5V 4.5A, 5V 3.6A, 9V 2.5A, 12V 2A(24W Max)
Type-C output: 5V 3.6A, 9V 3A, 12V 2.25A, 20V 2.25A(45W Max)
Cigarette lighter output: 60W Max (Cigarette lighter not supported)
USB total output: 27W+18W+45W (USB3/Type-C shared); (90W) (Max)
Host size: about 61.4*60.4*31mm
Car charger size: about 95.3*31.3*34.3mm
Color: Black



Material: PC flame retardant
Protocol: USB1 Port: QC2.0/QC3.0/AFC/FCP/SCP/SFCP/
MTK PE+1.1/PE+2.0; USB2 Port: QC2.0/QC3.0/
AFC/FCP/SCP/SFCP/MTK PE+1.1/PE+2.0; Type-C Port: QC2.0/
QC3.0/AFC/FCP/PD2.0/PD3.0/PPS USB Port: 3 X USB
USB1/2 Output: 4.5V=5A, 5V=4.5A, 5V 3.6A, 9V 2.5A,
12V=2A(24W Max) Type-C Output: 5V 3.6A, 9V 3A, 12V 2.25A,
20V=2.25A(45W Max) Total output power: USB1/USB2
(shared 24W)+Type-C(45W) Size: 20.6 X 86 X 20.6mm
Weight: 28g Color: Metal Gray



Material: Aluminum alloy
Protocol: Support PD2.0, QC3.0/QC2.0, FCP, AFC,
PPS and other charging protocols.
Input: DC12~24V
Type-C 1 output: 5V/3A,9V/2.22A,12V/1.67A(20W Max)
Type-C 2 output: 5V/3A,9V/2.22A,12V/1.67A(20W Max)
PPS: 3.3~11V/2A (22W Max)
Simultaneous use of Type-C+Type-A: 20W+20W(Max)
Size: 25.5*60.8*25.5mm Weight: 27g Color: Metal Grey/ Green



Input: DC12-24V
USB1 port output: 5V/3A,9V/2A,12V/1.5A (18W Max)
USB2 port output: 5V/3A, 9V/2A, 12V/1.5A (18W Max)
USB1 port + USB2 simultaneous output
total power: 5V/3.4A Max
Ports: 2-USB Product size: 28.2*57.1*28.2mm
Product weight: 17g
Working temperature: - 10℃ - 50℃
Color: Translucent brown & Translucent blue



Input: DC12-24V
USB-A port output: 5V/3A,9V/2A, 12V/1.5A (18W Max)
USB-C port output: 5V/3A9V/3A, 12V/2.5A (30W Max)
PPS : 3.3V-11V/3A (33W Max)
USB-A+USB-C output at the same time
Total power: 5V/3.4A Max Ports:2-USB
Product size: 28.2*57.1*28.2mm
Product weight: 16.5g
Working temperature: -10℃ - 50℃
Color: Translucent brown & Translucent blue



HOT

30w
(max)



CC532

Input: 12-24V, DC 3.5A
USB Output: DC 5V=3A, 9V=2A, 12V=1.5A (18W)
Type-C Output: DC 5V=3A, 9V=3A, 12V=2.5A (30W)
Total Output: DC 5V=3.0A Max
Ports: 2-USB Product Size: 25 * 48 * 25mm
Product Weight: 14.5g
Working Temperature: -10°C - 65°C
Color: Black/White



CC533

Input: 12-24V DC 2A
Output: DC 5V=2.4A
Ports: 2-USB
Size: 25 * 48 * 25mm
Weight: 14.1g
Working temperature: -10°C - 65°C
Color: Black/White



30w
(max)



CC534

Input: 12-24V, DC 3.5A
USB Output: DC 5V=3A, 9V=2A, 12V=1.5A (18W)
Type-C Output: DC 5V=3A, 9V=3A, 12V=2.5A (30W)
Total Output: DC 5V=3.0A Max
Ports: 2-USB
Product Size: 23.6 * 42.6 * 23.6mm
Product Weight: 11g
Working Temperature: -10°C - 65°C
Color: Transparent Brown & Transparent



18w
(max)



CC535

Input: 12-24V DC 2A
Output: DC 5V=3A, 9V=2A, 12V=1.5A (18W)
Port: 1-USB
Size: 25 * 48 * 25mm
Weight: 11g
Working temperature: -10°C - 65°C
Color: Transparent Brown & Transparent



18w
(max)



CC536

Input: DC 12-24V
Output: DC 5V/3A, 9V/2A, 12V/1.5A (18W)
Port: 1-USB
Size: 24.7 * 53.3 * 24.7mm
Weight: 16.3g
Working temperature: -10°C - 55°C
Color: Grey



CC537

36W

36w
(max)



CC537

Input: DC 12-24V
USB1 Output: 5V/3A, 9V/2A, 12V/1.5A, 18W MAX
USB2 Output: 5V/3A, 9V/2A, 12V/1.5A, 18W MAX
USB-1+USB-2 common output: 36W Max
Ports: 2-USB Product Size: 25 * 62.5 * 25mm
Product Weight: 23.4g
Working Temperature: -10°C - 55°C
Color: grey



HOT

10W
(max)



CC538

Input: 12-24V, DC 3.5A
USB Output: DC 5V=3A, 9V=2A, 10V=2.25A (18W),
12V=3A, 20V=3A (60W Max)
Type-C1/C2 Output: 5V=3A, 9V=3A, 12V=3A,
15V=3A, 20V=5A, 3.3~21V=5A (100W Max)
USB+Type-C2 output: 5V=3.4A Product Size: 43.8*43.8*79.3mm
Product Weight: 56.6g Working Temperature: -10°C - 55°C
Color: Black



Fast charge agreement



Security Protocol



fast charging



CC539

Input: 12-24V
USB Output: DC 5V=3A, 9V=2.5A, 12V=2.5A (30W Max)
Type-C Output: DC 5V=3A, 9V=2.5A, 12V=2.5A (30W Max)
USB-A+USB-C output: 5V 3A (Max) iP cable output:
9V=3A (27W Max) Type-C cable output: 5V=3A, 9V=3A, 12V=3A,
15V=3A, 20V=3A, 3.3V~11V=3A; 3.3~21V=3A (60W Max)
Product Size: 57.3*32.2*122.9mm Product Weight: 112.9g
Working Temperature: -10°C - 55°C



Fast charge agreement



Security Protocol



fast charging



33W
(max)



CC541

Input: 12-24V
Type-C Output: DC 5V=3A, 9V=3A,
12V=2.5A (30W) PPS: 3.3~11V=3A (33W)
Product Size: 25.3*27.2*46.7mm
Product Weight: 15.9g
Working Temperature: -10°C - 55°C



Fast charge agreement



Security Protocol



fast charging



33W
(max)



CC542

Input: 12-24V
USB output: DC 5V=3A, 9V=2A, 12V=1.5A (18W)
Type-C output: DC 5V=3A, 9V=3A,
12V=2.5A (30W) PPS: 3.3~11V=3A (33W)
Size: 25.3*26.4*52.7mm
Weight: 20.2g
Working temperature: -10°C - 55°C



Fast charge agreement



Security Protocol



Super fast charging



33W
(max)



CC543

Input: DC 12-24V
Type-C1 output: DC 5V=3A, 9V=3A, 12V=2.5A
Type-C2 output: DC 5V=3A, 9V=3A,
12V=2.5A PPS: 3.3~11V=3A
Total power: 30W+30W Max
Size: 25.1*25.1*61.5mm Weight: 26.2g
Working temperature: -10°C - 55°C



Fast charge agreement



Security Protocol



Super fast charging



CC539



FM01

Shell material: ABS+PC+ TPE
Input voltage: DC 5V Bluetooth version: V5.0
Bluetooth distance: ≤10 meters TF card capacity: ≤64GB
Cable length: about 1.2m Product size: about 68*31*16mm
Product weight: 33g
TF card support format: MP3 / WAV / FLAC / WMA
Color: Black



48w

Total Output Power



FM02

Wireless version: V5.0 Wireless distance: ≤10m
Wireless frequency: 2.4GHz FM operating frequency:
88.1-107.9MHz FM effective transmission distance: ≤5m
Support MP3/WMA/WAV/FLAC/APE and other audio formats
Input: DC12-24V USB output: 5V/3A, 9V/2A,
12V/1.5A (18W Max) Type-C output: 5V/3A, 9V/3A, 12V/2.5A,
15V/2A, 20V/1.5A (30W Max) PPS: 3.3-11V/3A Max
USB-A+Type-C total output: 48W (18W+30W)
Ports: 2-USB Size: 49 X 72 X 41mm Weight: 32g
Color: Dark grey/Purple



New

48w

Total Output Power



FM03

Wireless version: V5.0 Wireless distance: ≤10m
Wireless frequency: 2.4GHz
FM operating frequency: 88.1-107.9MHz
FM effective transmission distance: ≤5 meters
Support MP3/WMA and other audio formats
Wireless support A2DP/AVRCP/HFP/HSP and other modes
Support TF card/U disk capacity: ≤64GB
Input: DC12-24V USB output: 5V/3A, 9V/2A, 12V/1.5A (18W Max)
Type-C output: 5V/3A, 9V/3A, 12V/2.5A (30W Max)
PPS: 3.3-11V/3A Max USB-A+Type-C total output:
48W (18W+30W) Ports: 2-USB Product size: 42*85*52mm
Product weight: 45.3g Working temperature: -10°C - 40°C
Color: Black



VIDVIE

<https://vidvietech.com/>

Foshan
Office: D1-03, Building D, Nanhai New Economic Industry Center,
No. 1 Xianan Road, Guicheng Street, Nanhai District, Foshan City, Guangdong

Shop NO.1 : No. 127, the 1st floor, Guangzhou the thirteen-hongs Culture and Technology Center, Exhibition
Building on the right side of New Asia, No. 37 Xidi Erma Road, Liwan District, Guangzhou

Shenzhen
RmY2-5F-03, No.5 Creative Zone, Yayuan Road, Bantian Street, Longgang District, Shenzhen, China

Shop NO.2 : A46-47, 1/F, Yale Smart Wearable International Market, Block D, Electronic & Technology Building,
Huaqiang North, Shenzhen

Contact Us:

✉ business@vidvietech.com

☎ +86 18565066884

☎ Rain-VIDVIE



VIDVIE® is a registered trademark, owned by Shenzhen Aifeng Chengpin Trading Co., Ltd. Shenzhen Aifeng Chengpin Trading Co., Ltd. has all the right to interpret matters related to this album.
The products displayed in the VIDVIE full-category product catalog are new products as of January 2021. New products on the shelves after January 2021 are not in this catalog. You can consult our sales staff for the latest product information.
If the products shown in this album are revised in the future, please refer to the information provided by the salesperson of our company. This album is for reference only.