

VIDVIE PRODUCT CATALOG

VIDVIE

<https://vidvietech.com/>

Foshan
Office: D1-03, Building D, Nanhai New Economic Industry Center,
No. 1 Xianan Road, Guicheng Street, Nanhai District, Foshan City, Guangdong

Shop NO.1 : No. 127, the 1st floor, Guangzhou the thirteen-hongs Culture and Technology Center, Exhibition
Building on the right side of New Asia, No. 37 Xidi Erma Road, Liwan District, Guangzhou

Shenzhen
RmY2-5F-03, No.5 Creative Zone, Yayuan Road, Bantian Street, Longgang District, Shenzhen, China

Shop NO.2 : A46-47, 1/F, Yale Smart Wearable International Market, Block D, Electronic & Technology Building,
Huaqiang North, Shenzhen

Contact Us:

✉ business@vidvietech.com

☎ +86 18565066884

🗣 Rain-VIDVIE

Super Design. Top Life >>>

EUROPEAN PLUG CHARGER



PLE216

Input: AC 100V~240V~50/60Hz 0.3A
Output: 5V / 2.4A
Size: 83 X 40 X 26mm
Ports: 2 X USB
Working Temperature: -10°C - 50°C

12W



PLE218

Input: AC 100V~240V~50/60Hz 0.3A
Output: 5V / 2.4A
Size: 60 X 48 X 66mm
Ports: 2 X USB
Working Temperature: -10°C - 50°C

12W



PLE219

Input: AC 100V~240V~50/60Hz 0.3A
Output: 5V / 2.4A
Size: 47 X 25 X 88mm
Ports: 2 X USB
Working Temperature: -10°C - 50°C

12W



PLE223Q

Input: AC 100V~240V~50/60Hz 0.5A
Output: 5V / 3A, 9V / 2A, 12V / 1.5A (18W MAX)
Size: 45.5 X 89.5 X 27mm
Ports: 1 X USB
Working Temperature: -10°C - 50°C




PLE230C

Input: AC 100V~240V~50/60Hz 0.7A
Output: USB-A: 5V / 3A, 9V / 2A, 12V / 1.5A
TYPE-C: 5V / 3A, 9V / 2.25A, 12V / 1.6A (20W MAX)
Size: 87 X 48 X 30.5mm
Ports: 2 X USB
Working Temperature: -10°C - 50°C

PD

20W



PLE231

Input: AC 100V~240V~50/60Hz 0.7A
Output: USB-A: 5V / 4.8A
Size: 87 X 48 X 30.5mm
Ports: 3 X USB
Working Temperature: -10°C - 50°C



PLE236C

Input: AC 100V~240V~50/60Hz 0.5A
Output: 5V / 3A, 9V / 2.2A, 12V / 1.67A (20W MAX)
Size: 35 X 68.5 X 33mm
Ports: 1 X USB
Weight: 40.5g
Working Temperature: -10°C - 50°C

PD

20W



PLE237C-Q

Input: AC 100~240V, 0.8A Max
USB-A output: DC 5V/4A, 9V/3A, 12V/2.5A
Type-C output: DC 5V/3A, 9V/3A, 12V/2.5A, 15V/2A, 20V/1.5A
PPS: DC 11V/3A 33W Max
USB-A+Type-C output: 5V/3A
Size: 82.2 X 43.5 X 25.7mm
Ports: 2 X USB
Working Temperature: 0°C - 40°C



PD

33W

QC 4.0





PLE240

Input: AC 100~240V, 50/60Hz 0.3A
Output: DC 5V / 2.4A (MAX)
Size: 44.7 X 26.8 X 80.8mm
Ports: 2 X USB
Working Temperature: -10°C - 50°C

12W



33W GaN



PLE241C

Input: 100V~240V~50/60Hz 0.8A Max
Output: USB-C 5V/3A, 9V/3A, 12V/2.5A, 15V/2A, 20V/1.5A
PPS: 3.3V-11V/3A 33W Max
Size: 31 X 68 X 32mm
Port: 1 X USB
Working Temperature: -10°C - 50°C

33W



67W GaN
22.5W USB-A



PLE242

Input: AC 100V~240V~50/60Hz, 1.5A(Max)
Output: USB-C1/C2: 5V==3A, 9V==3A, 12V==3A, 15V==3A, 20V==3.35A, 67W(Max)
USB-A: 4.5V==5A, 5V==4.5A, 9V==2A, 12V==1.5A 22.5W(MAX)
USB-C1+USB-C2: 45W+20W 65W(Max)
USB-C1+USB-A: 45W+18W 63W(Max)
USB-C2+USB-A: 5V==3.6A 18W(Max)
USB-C1+USB-C2+USB-A1: 45W+18W 63W(Max)
PPS: 3.3-20.3V/3.3A Size: 31.8 X 95.3 X 37mm
Ports: 3 X USB
Working Temperature: 0°C - 40°C



20W
QC 18W



PLE243

Input: AC 110V~240V
Output: USB-A: DC 5V/2.4A, 9V/2A, 12V/1.5A (18W)
Type-C: DC 5V/2.4A, 9V/2.22A, 12V/1.5A (20W)
USB-A+Type-C output: 20W
Size: 80 X 40 X 27mm
Ports: 2 X USB
Working Temperature: 50°C ±3°C

PD 20W **Qualcomm Quick Charge 3.0**





40W
GaN



EU PLE246

Input: AC 100V-240V-50/60Hz, 1.2A(Max)
Output: USB-C1: 5V=3A, 9V=3A, 12V=3A, 15V=2.5A, 20V=2A 40W(Max) PPS: 3.3V-11V=3A
USB-C2: 5V=3A, 9V=3A, 12V=3A, 15V=2.5A, 20V=2A 40W(Max) PPS: 3.3V-11V=3A
USB-C1+USB-C2 total output:
PD 25W+PD 15W or PD 35W+5W or PD 20W+PD 20W
Size: 40.9 X 80.9 X 30.9mm Ports: 2 X USB
Working Temperature: 0°C - 40°C

40W



20W



EU PLE248

Input: AC 100-240V, AC 50/60Hz
USB-A output: DC 5V=3A, 9V=2.22A, 12V=1.67A
Type-C output: DC 5V=3A, 9V=2.22A, 12V=1.67A
USB-A+Type-C output: DC 5V=3A
Ports: 2-USB
Product size: 49*80*38.7mm
Product weight: 42.35g
Working temperature: -10°C - 70°C

20W



QC 3.0



EU PLE249

Input: AC 100-240V, AC 50/60Hz
Output: QC 3.0 5V=3A, 9V=2A, 12V=1.5A
Port: 1-USB
Product size: 49*80*38.7mm
Product weight: 39.9g
Working temperature: -10°C - 70°C

QC 3.0



EU PLE244

Input: AC 110-240V
Output: DC 5V/2.4A (MAX)
Size: 44 X 26 X 63mm
Ports: 1 X USB
Working Temperature: -10°C - 50°C

12W



EU PLE245

Input: AC 110-240V
Output: DC 5V / 2.4A (MAX)
Size: 44 X 26 X 63mm
Ports: 2 X USB
Working Temperature: -10°C - 50°C

12W



EU PLE250

Input: AC 100-240V, AC 50/60Hz
Output: DC 5V=2.4A
Ports: 2-USB
Product size: 49*80*38.7mm
Product weight: 36.2g
Working temperature: -10°C - 70°C

12W



67W
GaN



EU PLE251

Input: AC 100V-240V-50/60Hz, 1.5A(Max)
Output: USB-C1: 5V=3A, 9V=3A, 12V=3A, 15V=3A, 20V=3.35A (67W Max)
USB-C2: 5V=3A, 9V=3A, 12V=3A, 15V=3A, 20V=3.35A (67W Max)
PPS: 3.3V-11V/4.5A USB-C1+USB-C2: PD45W+PD20W
USB-C1+USB-C2: 67W Max. Ports: 2-USB
Product size: 44*84*39mm Product weight: 107g
Color: White Working temperature: 0°C - 40°C

67W





PLE247

Input: 100-240V~50/60Hz, 2.5A Max.
Output: USB-C1: 5V≡3A, 9V≡3A, 12V≡3A, 15V≡3A, 20V≡5A, 100W(Max) USB-C2: 5V≡3A, 9V≡3A, 12V≡3A, 15V≡3A, 20V≡5A, 100W(Max) PPS: 3.3~11V≡3A
USB-A1: 4.5V≡5A, 5V≡4.5A, 5V≡3A, 9V≡2A, 12V≡1.5A, 22.5W(Max) USB-A2: 4.5V≡5A, 5V≡4.5A, 5V≡3A, 9V≡2A, 12V≡1.5A, 22.5W(Max) USB-C1+USB-C2: 65W+30W 95W(Max) USB-C1+USB-A1: 65W+18W 83W(Max) USB-C1+USB-A2: 65W+18W 83W(Max) USB-C2+USB-A1: 65W+18W 83W(Max) USB-C2+USB-A2: 65W+18W 83W(Max) USB-A1+USB-A2: 22.5W(Max) USB-C1+USB-C2+USB-A1: 45W+30W+18W 93W(Max) USB-C1+USB-C2+USB-A2: 45W+30W+18W 93W(Max) USB-C1+(USB-A1+USB-A2): 65W+22.5W 87.5W(Max) USB-C2+(USB-A1+USB-A2): 65W+22.5W 87.5W(Max) USB-C1+USB-C2+(USB-A1+USB-A2): 45W+30W+22.5W 97.5W (Max) Ports: 4-USB
Product size: 85*85*26.3mm Product weight: 277g
Working temperature: -10 °C~50 °C

PLE247

New

PD
20W



PLE253

Input: 100-240V~50/60Hz 0.8A(Max)
Output: 5V≡3A, 9V≡2.22A, 12V≡1.67A 20W
Port: 1 X Type-C
Product size: 72*32.5*32.5mm
Product weight: 42.9g
Working temperature: 0 °C~40 °C

20W



New

PD
33W



PLE254

Input: 100-240V~50/60Hz 0.8A(Max)
Output: 5V≡3A, 9V≡3A, 12V≡2.5A, 15V≡2A, 20W≡1.5A
Port: 1 X Type-C PPS: 3.3V~11V 3A 33W Max
Product size: 72*32.6*32.5mm
Product weight: 48.8g
Working temperature: 0 °C~40 °C

33W



New

PD
33W

USB
30W



PLE255

Input: 100-240V~50/60Hz 0.8A(Max)
Type-C Output: 5V≡3A, 9V≡3A, 12V≡2.5A, 15V≡2A, 20W≡1.5A
USB Output: 5V≡3A, 9V≡3A, 12V≡2.5A, 15V≡2A, 20W≡1.5A
Port: Type-C+USB PPS: 3.3V~11V 3A 33W Max
Product size: 72*32.5*32.5mm
Product weight: 46.6g
Working temperature: 0 °C~40 °C

33W



New

PD
20W



PLE256

Input: AC 100-240V~50/60Hz 0.8A Max
Output: 5V≡3A, 9V≡2.22A, 12V≡1.67A, 20W
Total power: 20W Max Interface: Type-C
Product size: 48*43*64mm
Product weight: 53.8g
Working temperature: 0 °C ~ 40 °C

20W



New

PD
33W



PLE257

Input: AC 100-240V~50/60Hz 0.8A Max
Output: 5V≡3A, 9V≡3A, 12V≡2.5A, 15V≡2A, 20V≡1.5A
PPS: 3.3V~11V≡3A 33W Max Total power: 33W Max
Interface: Type-C Product size: 48*43*64mm
Product weight: 53.8g
Working temperature: 0 °C ~ 40 °C

33W



New

PD
33W

USB
30W



PLE258

Input: 100-240V~50/60Hz 0.8A Max
Type-C Output: 5V≡3A, 9V≡3A, 12V≡2.5A, 15V≡2A, 20V≡1.5A PPS: 3.3V~11V 3A 33W Max
USB Output: 5V≡3A, 9V≡3A, 12V≡2.5A, 15V≡2A, 20V≡1.5A Total power: 33W Max
Interface: Type-C Product size: 48*43*64mm
Product weight: 53.8g
Working temperature: 0 °C ~ 40 °C

33W





PLE259

Input: 100-240V~50/60Hz 1.5A Max.
 USB-C1 output: 5V≡3A, 9V≡3A, 12V≡3A, 15V≡3A, 20V≡3.5A (70W)
 USB-C2 output: 5V≡3A, 9V≡3A, 12V≡3A, 15V≡3A, 20V≡3.5A (70W)
 USB-A1 output: 5V≡3A, 9V≡3A, 12V≡2.5A, 15V≡2A, 20V≡1.5A (30W)
 USB-A2 output: 5V≡3A, 9V≡3A, 12V≡2.5A, 15V≡2A, 20V≡1.5A (30W)
 Total output: 47W+5V≡3.1A
 Size: 85*85*27mm
 Product weight: 134.5g
 Operating temperature: -10°C-50°C

PLE259



PLE261

New
 PD
 33W



PLE260

Input: AC 100-240V 50/60Hz 0.5A
 Type-C1 output: DC 5V≡3A, 9V≡3A, 12V≡2.5A(30W)
 PPS: 3.3-11V≡3A 33W
 Type-C2 output: DC 5V≡3A, 9V≡3A, 12V≡2.5A(30W)
 PPS: 3.3-11V≡3A 33W
 Type-C1+Type-C2 output: DC 5V≡3A (15W)
 Product size: 30.6*43.2*79.5mm Product weight: 58.23g
 Working temperature: 0°C - 40°C

33W



New
 PD
 45W



PLE261

Input: AC 100-240V 50/60Hz 0.5A
 Type-C1 output: DC 5V≡3A, 9V≡3A, 12V≡3A, 15V≡3A, 20V≡2.25A (45W) PPS: 3.3-11V≡3A 33W
 Type-C2 output: DC 5V≡3A, 9V≡3A, 12V≡3A, 15V≡3A, 20V≡2.25A (45W) PPS: 3.3-11V≡3A 33W
 Type-C1+Type-C2 output: 25W+20W
 Product size: 47.5*30.7*84.5mm Product weight: 79.7g
 Working temperature: 0°C - 40°C

45W



New
 MAX
 65W
 USB
 22.5W



PLE262

Input: 110-240V~50/60Hz 1.5A Max
 Type-C1/Type-C2 output: DC 5V≡3A, 9V≡3A, 12V≡3A, 15V≡3A, 20V≡3.25A(65W Max)
 USB output: DC 5V≡3A, 9V≡2.5A, 12V≡1.87A(22.5W Max)
 Type-C1+Type-C2 output: 45W+20W(65W Max)
 Type-C1+USB output: 45W+18W(63W Max)
 Type-C2+USB output: DC 5V≡2.4A+DC 5V≡2.4A(24W Max)
 Type-C1+Type-C2+USB output: 45W+10W+10W(65W Max)
 Product size: 56.3*29*97mm Product weight: 131.2g
 Working temperature: 0°C - 40°C

65W





PLM361

New

PD
33W



PLM360

Input: AC 100-240V 50/60Hz 0.5A
Type-C1 output: DC 5V=3A, 9V=3A, 12V=2.5A(30W)
PPS: 3.3-11V=3A 33W
Type-C2 output: DC 5V=3A, 9V=3A, 12V=2.5A(30W)
PPS: 3.3-11V=3A 33W
Type-C1+Type-C2 output: DC 5V=3A (15W)
Product size: 30.6*43.2*58.7mm Product weight: 52g
Working temperature: 0°C - 40°C

33W



New

PD
45W



PLM361

Input: AC 100-240V 50/60Hz 0.5A
Type-C1 output: DC 5V=3A, 9V=3A, 12V=3A, 15V=3A, 20V=2.25A (45W) PPS: 3.3-11V=3A 33W
Type-C2 output: DC 5V=3A, 9V=3A, 12V=3A, 15V=3A, 20V=2.25A (45W) PPS: 3.3-11V=3A 33W
Type-C1+Type-C2 output: 25W+20W
Product size: 47.5*30.7*63.7mm Product weight: 81.4g
Working temperature: 0°C - 40°C

45W



New

MAX
65W

USB
22.5W



PLM362

Input: 110-240V~50/60Hz 1.5A Max
Type-C1/Type-C2 output: DC 5V=3A, 9V=3A, 12V=3A, 15V=3A, 20V=3.25A(65W Max)
USB output: DC 5V=3A, 9V=2.5A, 12V=1.87A(22.5W Max)
Type-C1+Type-C2 output: 45W+20W(65W Max)
Type-C1+USB output: 45W+18W(63W Max)
Type-C2+USB output: DC 5V=2.4A+DC 5V=2.4A(24W Max)
Type-C1+Type-C2+USB output: 45W+10W+10W(65W Max)
Product size: 56.3*29*75mm Product weight: 117.8g
Working temperature: 0°C - 40°C

65W



TA4404

New

MAX
2.4A



TA4403

Material: ABS+PC
Rating: 100-250V 10A Max, 2500W
Maxinput: 100-250V 50-60Hz 0.5A
USB output: 5.0V-2.4A
USB-A+USB-C output: 2.4A 12W Max
Rating: 10A MAX. Size: 70*47*53.5mm
Weight: 134.7g Working temperature: -10-45°C

2.4A



New

PD
20W



TA4404

Material: ABS+PC
Type-C output: 5V=3A, 9V=2.22A, 12V=1.67A 20W MAX
USB output: 5V=3A, 9V=2A, 12V=1.5A 18W MAX
Type-C+USB total output: 5V 3A MAX
Fuse rating: 8A MAX
Maximum power: 880W at 110V/1840W at 230V
Product size: 68.42*54.78*52.65mm
Product weight: 136.68g
Colour: Black Working temperature: 0°C - 40°C

20W





TA4405



TA4407

New

OUT
25W



TA4405

USB Input: 100-240V~50/60Hz 0.8A
Type-C output: 3.3-11V=2.25A(PPS) 5V=3A, 9V=2.77A, 12V=2.08A(25W) USB output: 5V=3A, 9V=2.22A, 12V=1.67A(20W)
Type-C+USB output: 15W Max Product size: 42*70*25.4mm
Product weight: 64.5g
Working temperature: 0°C - 40°C

20W 25W



New

OUT
65W



TA4407

Type-C1 output: 3.3-11V 3A, 5V/9V/12V/15V=3A, 20V=3.25A (65W Max) Type-C2 output: 3.3-11V=3A, 5V/9V/12V/15V=3A, 20V=3.25A (65W Max)
USB output: 4.5V=5A, 5V=4.5A, 9V=3A, 12V=2.5A, 20V=1.5A (30W Max)
Type-C1+Type-C2 output: 45W+18W (63W Max)
Type-C1+Type-C2+USB output: 45W+5V 3A (60W Max)
Total output: 65W Max Product size: 54*78*52.3mm
Product weight: 195.1g Working temperature: 0°C - 40°C

65W



New

OUT
33W



TA4406

Input: 100-240V~50/60Hz 0.8A
Type-C output: 5V=3A, 9V=3A, 12V=2.5A, 15V=2A, 20V=1.5A(30W)
PPS: 5.5-11V=3A 33W Product size: 42*70*25.4mm
Product weight: 64g
Operating temperature: 0°C - 40°C

33W



New

OUT
100W




TA4408

Type-C1/C2/C3 out: 3.3-21V=5A(PPS)
Type-C1/C2/C3 output: 5V/9V/12V/15V=3A, 20V=5A (100W) USB output: 5V/9V/12V/20V=3A (60W)
Type-C1+C2+(C3+USB) output: 65W+20W+15W
Type-C1+C2+C3 output: 60W+20W+20W
Type-C1+USB / C2+USB output: 70W+30W
Type-C1+(C3+USB) / C2+(C3+USB) output: 80W+15W
Type-C3+USB output: 15W Max Product size: 55*100*53mm
Product weight: 297.2g Working temperature: 0°C - 40°C

100W



CHARGER



EUROPEAN PLUG CHARGER





XL-PLE218

Material: PC flame retardant
Input: AC 100V~240V~50/60Hz 0.7A
Output: USB-A: 5V / 3A, 9V / 2A, 12V / 1.5A (QC 18W)
TYPE-C: 5V / 3A, 9V / 2.25A, 12V / 1.6A (PD 20W MAX)
Size: 80 X 40.2 X 27mm
Ports: 2 X USB Color: Black

20W   





XL-PLE219

Material: PC flame retardant
Input: AC 100V~240V~50/60Hz 0.3A
Output: 5V / 2.4A
Size: 80 X 40.2 X 27mm
Ports: 2 X USB
Color: Black

12W 





XL-PLE222

Input: 100~240V~50/60Hz 1.5A Max
Output: Type-C1/C2: 5V=3A, 9V=3A, 12V=3A, 15V=3A, 20V=3.5A
PPS: 3.3V~11V=5A USB1/2: 5V=3A, 9V=3A, 12V=2.5A, 15V=2A, 20V=1.5A Type-C1+C2: 45W(PPS: 3.3V~11V=4.05A)+20W
Type-C1+USB1/2: 45W+18W Type-C2+USB1/2: 5V=3.6A 18W
USB1+USB2: 5V=3.6A 18W Type-C1+Type-C2+USB1+USB2: 45W+5V=3.6A 18W Size: 48.5*96*43mm Product weight: 139.3g
Operating temperature: -10°C~50°C

70W  





XL-PLE223

Input: 100~240V~50/60Hz 1.5A Max
Output: Type-C1/C2: 5V=3A, 9V=3A, 12V=3A, 15V=3A, 20V=3.5A
PPS: 3.3V~11V=5A USB1/2: 5V=3A, 9V=3A, 12V=2.5A, 15V=2A, 20V=1.5A Type-C1+C2: 45W(PPS: 3.3V~11V=4.05A)+20W
Type-C1+USB1/2: 45W+18W Type-C2+USB1/2: 5V=3.6A 18W
USB1+USB2: 5V=3.6A 18W Type-C1+Type-C2+USB1+USB2: 45W+5V=3.6A 18W Size: 42*69*35mm Product weight: 215g
Operating temperature: -10°C~50°C

70W  



VIDVIE

<https://vidvietech.com/>

Foshan
Office: D1-03, Building D, Nanhai New Economic Industry Center,
No. 1 Xianan Road, Guicheng Street, Nanhai District, Foshan City, Guangdong

Shop NO.1 : No. 127, the 1st floor, Guangzhou the thirteen-hongs Culture and Technology Center, Exhibition
Building on the right side of New Asia, No. 37 Xidi Erma Road, Liwan District, Guangzhou

Shenzhen
RmY2-5F-03, No.5 Creative Zone, Yayuan Road, Bantian Street, Longgang District, Shenzhen, China

Shop NO.2 : A46-47, 1/F, Yale Smart Wearable International Market, Block D, Electronic & Technology Building,
Huaqiang North, Shenzhen

Contact Us:

✉ business@vidvietech.com

☎ +86 18565066884

☎ Rain-VIDVIE

VIDVIE

Smart phone accessories

VIDVIE® is a registered trademark, owned by Shenzhen Aifeng Chengpin Trading Co., Ltd. Shenzhen Aifeng Chengpin Trading Co., Ltd. has all the right to interpret matters related to this album.

The products displayed in the VIDVIE full-category product catalog are new products as of January 2021. New products on the shelves after January 2021 are not in this catalog. You can consult our sales staff for the latest product information. If the products shown in this album are revised in the future, please refer to the information provided by the salesperson of our company. This album is for reference only.