

VIDVIE PRODUCT CATALOG

VIDVIE

<https://vidvietech.com/>

Foshan
Office: D1-03, Building D, Nanhai New Economic Industry Center,
No. 1 Xianan Road, Guicheng Street, Nanhai District, Foshan City, Guangdong

Shop NO.1 : No. 127, the 1st floor, Guangzhou the thirteen-hongs Culture and Technology Center, Exhibition
Building on the right side of New Asia, No. 37 Xidi Erma Road, Liwan District, Guangzhou

Shenzhen
RmY2-5F-03, No.5 Creative Zone, Yayuan Road, Bantian Street, Longgang District, Shenzhen, China

Shop NO.2 : A46-47, 1/F, Yale Smart Wearable International Market, Block D, Electronic & Technology Building,
Huaqiang North, Shenzhen

Contact Us:


✉ business@vidvietech.com

☎ +86 18565066884

🌐 Rain-VIDVIE

Super Design. Top Life >>>

POWER BANK



PB747

Capacity: 10000mAh
Battery Type: Polymer core
Input: Micro: 5V / 2.4A 12W MAX
Type-C: 5V / 2.4A 12W MAX
Output: USB1 / 2: 5V / 2.4A 12W MAX
Size: 140 X 68 X 16mm
Material: ABS
Color: White

10000mAh



HOT



PB759

Capacity: 10000mAh
Battery Type: Polymer core
Input: Micro: 5V / 2A 10W MAX
Type-C: 5V / 2A 10W MAX
Output: USB-A1-2: 5V / 2.1A
Size: 67.8 X 140 X 15.7mm
Material: ABS+Polymer batteries
Weight: 221.5g Color: White

10000mAh



HOT

PD 18W



PB760

Capacity: 10000mAh
Battery Type: Polymer core
Input: Micro: 5V / 2.4A, 9V / 2A
Type-C: 5V / 2.4A, 9V / 2A, 18W PD
Output: USB1: 5V / 3A, 9V / 2A, 12V / 1.5A
Type-C: 5V / 3A, 9V / 2A, 12V / 3A, 15V / 1.5A, 18W PD
Size: 66.5 X 139 X 15.8mm
Weight: 220.5g
Material: ABS Color: White

10000mAh

PD 18W


Qualcomm Quick Charge 3.0



PB766

Capacity: 20000mAh
Rated capacity: 12500mAh
Battery Type: Polymer core
Micro-USB input: DC 5V/2A
Type-C input: DC 5V/2A
USB1 output: DC 5V/2.1A
USB2 output: DC 5V/2.1A
Size: 67 X 139.5 X 28mm Weight: 407.1g
Material: ABS Color: white

20000mAh



PB758

Capacity: 10000mAh
Battery Type: ABS+Polymer batteries
Input: Micro: 5V / 2A
USB: 5V / 2A
Output: Micro: 5V/2A Type-C: 5V/2A
Lighting: 5V/2A
Size: 67.5 X 150 X 40mm
Material: ABS
Weight: 238g Color: White

10000mAh





PB765

Capacity: 10000mAh Rated capacity: 6200mAh
Battery Type: Polymer core
Type-C input: DC 5V/3A, 9V/2A, 18W(Max)
Type-C output: DC 5V/3A, 9V/2.23A, 12V/1.67A, 20W
USB output: DC 5V/4.5A, 4.5V/5A, 5V/3A, 9V/2A, 12V/1.5A, 22.5W
Lightning output: DC 5V/2A, 9V/2A, 18W(Max)
Wireless charging: 15W/10W/7.5W/5W
Size: 68 X 148 X 17.3mm Weight: 239.8g
Material: PC flame retardant + rubber oil Color: white

10000mAh **PD 20W** **22.5W** **15W**



PD 20W

22.5W



PB764

Capacity: 30000mAh/3.7V 111Wh Rated capacity: 18000mAh
Battery Type: Polymer core Material: PS+ABS
Micro input: DC 5V/3A, 9V/2A, 12V/1.5A(18W)
Type-C input: DC 5V/3A, 9V/2A, 12V/1.5A(18W)
USB1 output: DC 4.5V/5A, 5V/4.5A, 9V/2A, 12V/1.5A(22.5W)
USB2 output: DC 4.5V/5A, 5V/4.5A, 9V/2A, 12V/1.5A(22.5W)
Type-C output: DC 5V/3A, 9V/2.2A, 12V/1.67A(20W)
USB1+USB2 total output: DC 5V/3A Color: white
Product size: 70.7*153.5*40.5 mm Product weight: 606g

30000mAh **PD 20W** **22.5W**



PD 20W

22.5W



PB767

Model: PB767 Capacity: 10000mAh/37Wh
Rated capacity: 6300mAh Cell type: polymer
Shell material: PC flame retardant
Type-C input: DC 5V/3A, 9V/2A, 18W(Max)
Micro input: DC 5V/3A, 9V/2A, 12V/1.5A, 18W(Max)
Type-C output: DC 5V/3A, 9V/2.23A, 12V/1.67A, 20W(Max)
USB output: DC 5V/4.5A, 4.5V/5A, 5V/3A, 9V/2A, 12V/1.5A, 22.5W(Max)
Size: 68 X 140 X 16mm Weight: 223.8g
Color: white

10000mAh **22.5W** **PD 20W**



PD 20W

22.5W



PB768

Model: PB768 Capacity: 20000mAh/74Wh
Rated capacity: 12600mAh Cell type: polymer
Shell material: PC flame retardant
Type-C input: DC 5V/3A, 9V/2A, 18W(Max)
Micro input: DC 5V/3A, 9V/2A, 12V/1.5A, 18W(Max)
Type-C output: DC 5V/3A, 9V/2.23A, 12V/1.67A, 20W(Max)
USB output: DC 5V/4.5A, 4.5V/5A, 5V/3A, 9V/2A, 12V/1.5A, 22.5W(Max)
Size: 68 X 140 X 28mm Weight: 403.8g
Color: white

20000mAh **22.5W** **PD 20W**



PD 20W

22.5W

QC 3.0



PB769

Model: PB769 Capacity: 10000mAh/37Wh
Rated capacity: 6300mAh Cell type: polymer
Shell material: PC flame retardant
Type-C input: DC 5V/3A, 9V/2A, 18W(Max)
Type-C output: DC 5V/3A, 9V/2.23A, 12V/1.67A, 20W(Max)
USB output: DC 5V/4.5A, 4.5V/5A, 5V/3A, 9V/2A, 12V/1.5A, 22.5W(Max)
Size: 68 X 143 X 17mm Weight: 235g
Color: white

10000mAh **22.5W** **PD 20W** **QC 3.0**





PB771

VIDVIE Designed by VIDVIE HongKong Branch

10W
-CHARGING-

9:41

88% Charged



PB771

Capacity: 10000mAh/37Wh
Rated capacity: 6300mAh Cell type: polymer
Shell material: ABS+PC flame retardant
Type-C input: DC 5V/2A Micro input: DC 5V/2A
USB1/USB2 output: DC 5V/2A
Product size: 68 * 137 * 15.5mm
Product weight: 223.5g
Working temperature: -10 °C-50 °C

10000mAh 2A



PB772

Capacity: 10000mAh/37Wh
Rated capacity: 6300mAh Cell type: polymer
Shell material: ABS+PC flame retardant
Type-C input: DC 5V/2A Micro input: DC 5V/2A
USB1/USB2 output: DC 5V/2A
Product size: 68*140*16.5mm
Product weight: 218g
Working temperature: -10 °C-50 °C

10000mAh 2A



22.5W



PB776

Capacity: 10000mAh/37Wh Rated capacity: 5800mAh
Cell Type: Polymer Shell material: ABS+PC flame retardant
Type-C Input: DC 5V/3A, 9V/2A USB output: DC 4.5V/5A, 5V/4.5A
5V/3A, 9V/2A, 12V/1.5A (22.5W) Type-C output: DC 4.5V/5A, 5V/4.5A
5V/3A, 9V/2A, 12V/1.5A (22.5W) Lightning output: DC 5V/2.4A,
9V/2.23A Multi-port simultaneous total output: DC 5V/3A
Product size: 89.5*25.6*58.6mm Product weight: 192g
Working temperature: -10 °C-50 °C

10000mAh 22.5W



PB779

Battery capacity: 30000mAh Rated capacity: 19500mAh
Core type: Polymer Housing material: ABS+PC
Micro input: DC 5V/2A Type-C input: DC 5V/2A
USB1 output: DC 5V/2.1A USB2 output: DC 5V/2.1A
USB1+USB2 total output: DC 5V/2.1A Max
Product size: 68.3*146*41mm Product weight: 602g
Color: White Working temperature: -10 °C-50 °C

30000mAh 2.1A



PB773

Capacity: 10000mAh/37Wh
Rated capacity: 6300mAh Cell type: polymer
Shell material: ABS+PC flame retardant
Type-C input: DC 5V/2A Micro input: DC 5V/2A
USB1/USB2 output: DC 5V/2A
Product size: 68 * 137 * 15.5mm
Product weight: 222.5g
Working temperature: -10 °C-50 °C

10000mAh 2A



PB775

Capacity: 20000mAh/74Wh
Rated capacity: 12600mAh
Cell type: polymer
Shell material: ABS+PC flame retardant
Type-C input: DC 5V/2.1A
USB1/USB2 output: DC 5V/2.1A
Product size: 70.4*149.1*28.5mm
Product weight: 428g
Working temperature: -10 °C-50 °C

20000mAh





PD
100w
22.5W
3A



PB777

Battery: 21700 lithium battery * 4 Capacity: 20000mAh/74Wh
 Rated capacity: 12000mAh Material: fireproof ABS+PC
 Type-C output: DC 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/5A (100W)
 USB output: DC 4.5V/5A, 5V/4.5A, 5V/3A, 9V/2A, 12V/1.5A (22.5W)
 Type-C input: DC 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.25A (65W)
 USB-C+USB-A output: DC 5V/3A 15W
 Compatible with fast charging protocols: PD 2.0/3.0, PPS, QC2.0/3.0, AFC, FCP, SCP, VOOC, BC1.2, DCP
 Wired maximum power: PD 100W
 Product size: 166*53*45mm Product weight: 432.3g
 Working temperature: -10 °C-50 °C

20000mAh 100W 22.5W 3A



PD
100w
22.5W
3A



PB778

Battery: 21700 lithium battery * 8 Capacity: 40000mAh/148Wh
 Rated capacity: 21600mAh Material: fireproof ABS+PC
 Type-C output: DC 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/5A (100W)
 USB output: DC 4.5V/5A, 5V/4.5A, 5V/3A, 9V/2A, 12V/1.5A (22.5W)
 Type-C input: DC 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.25A (65W)
 USB-C+USB-A output: DC 5V/3A 15W
 Compatible with fast charging protocols: PD 2.0/3.0, PPS, QC2.0/3.0, AFC, FCP, SCP, VOOC, BC1.2, DCP
 Wired maximum power: PD 100W
 Product size: 166*54*67mm Product weight: 746.4g
 Working temperature: -10 °C-50 °C

40000mAh 100W 22.5W 3A





PB781T



PB782

New



PB781T

Capacity: 5000mAh
Rated capacity: 3000mAh
Battery type: 21700 lithium battery
Shell material: ABS+PC
Type-C input: DC 5V/2A
Type-C output: DC 5V/2.4A
Product size: 78*47.8*26.2mm
Product weight: 95.8g
Working temperature: -10°C-50°C

5000mAh



New



PB780

Battery capacity: 10000mAh/37Wh Rated capacity: 5800mAh
Core type: Polymer Housing material: ABS+PC
Type-C input: DC 12V/1.5A, 9V/2A, 5V/2.6A 18W
Type-C Output: DC 12V/1.66A, 9V/2.22A, 5V/3A 20W
Wireless charging output: 5W/7.5W/10W/15W
Product size: 67*106*19mm
Product weight: 210.8g
Color: Dark Gray
Working temperature: -10 °C-50 °C

10000mAh 20W 3A



New



PB781i

Capacity: 5000mAh
Rated capacity: 3000mAh
Battery type: 21700 lithium battery
Shell material: ABS+PC
Type-C input: DC 5V/2A
Lightning output: DC 5V/2.4A
Product size: 78*47.8*26.2mm
Product weight: 94.7g
Working temperature: -10°C-50°C

5000mAh



New



PB782

Capacity: 10000mAh
Rated capacity: 6300mAh
Cell Type: Polymer
Shell material: aluminum alloy
Micro input: DC 5V/2A Type-C output: DC 5V/2A
USB1 output: DC 5V/2.1A USB2 output: DC 5V/2.1A
Product size: 139*67*14.7mm
Product weight: 250g
Working temperature: -10°C-50°C

10000mAh 2.1A





New

PB783

Capacity: 10000mAh
 Rated capacity: 6000mAh Cell Type: Polymer
 Shell material: fireproof ABS+PC+liquid silicone
 Type-C input: DC 5V/3A, 9V/2.22A, 12V/1.67A
 Type-C output: DC 5V/3A, 9V/2A, 12V/1.5A
 Wired maximum power: PD 20W
 Wireless maximum power: 15W
 Product size: 99*67*20mm Product weight: 202g
 Working temperature: -10°C-50°C

10000mAh PD 20W



New

PB784

Capacity: 10000mAh/37Wh Rated capacity: 6300mAh
 Battery type: lithium polymer Shell material: ABS+PC
 Type-C input: 5V/3A, 9V/2A, 12V/1.5A(18W)
 USB output: 5V/3A, 9V/2A, 12V/1.5A(18W)
 Type-C output: 5V/3A, 9V/2.23A, 12V/1.67A(20W)
 Watch wireless charging: 2.5W
 Product size: 103*50*26mm
 Product weight: 179g
 Working temperature: -10°C-50°C

10000mAh



New

PB785

Capacity: 10000mAh/38.5Wh Rated capacity: 6300mAh(5V/2A)
 Battery type: polymer Shell material: ABS+PC
 Lightning input: 5V/2A, 9V/2A, 12V/1.5A, 18W
 Type-C input: 5V/2.5A, 9V/2A, 12V/1.5A, 18W
 Type-C output: 5V/3.1A, 9V/2.23A, 12V/1.67A, 20W
 PPS: 3-11V/2A 22W
 USB输出: 5V/4.5A, 5V/3A, 9V/2A, 12V/1.5A, 22.5W
 Product size: 78*47.8*26.2mm Product weight: 95.8g
 Working temperature: -10°C-50°C

10000mAh PD 20W



New

PB786

Capacity: 10000mAh Rated capacity: 6300mAh
 Cell Type: Polymer Shell material: Aluminum alloy + PC
 Type-C input: 5V/2.5A, 9V/2A, 12V/1.5A, 18W
 Type-C output: 5V/3.1A, 9V/2.23A, 12V/1.67A, 20W
 PPS: 3-11V/2A, 22W
 USB output: 5V/4.5A, 5V/3A, 9V/2A, 12V/1.5A, 22.5W
 Product size: 66.5*57.7*22.7mm
 Product weight: 173.8g
 Working temperature: -10°C-50°C

10000mAh PD 20W








PB787

Capacity: 10000mAh/37Wh
 Rated capacity: 6300mAh(5V/2A) Cell Type: Li-polymer
 Shell material: aluminum
 Type-C input: DC 5V=2.4A, 9V=2.0A (18W)
 Type-C output: DC 5V=2.4A, 9V=2.22A, 12V=1.67A (20W)
 Product size: 125.5*62.2*11.2mm Product weight: 177.3g
 Working temperature: -10°C-50°C




10000mAh

PD 20W




PB788

Capacity: 20000mAh/74Wh Rated capacity: 13000mAh(5V/2A)
 Battery type: Li-polymer Shell material: aluminum
 Type-C input: DC 5V=2.4A, 9V=2.0A, 12V=1.5 (18W)
 USB output: DC 5V=2.4A, 9V=2.0A, 12V=1.5A, 4.5V=5.0A, 5V=4.5A (22.5W)
 Type-C output: DC 5V=2.4A, 9V=2.22A, 12V=1.67A (20W)
 Product size: 128*63.9*22.3mm
 Product weight: 314.1g
 Working temperature: -10°C-50°C




20000mAh

PD 20W




PB789

Capacity: 5000mAh/18.25Wh Rated capacity: 3000mAh(5V/2A)
 Battery type: lithium polymer Shell material: aluminum+PC
 Type-C input: DC 5V=2.4A, 9V=2.0A (18W)
 Type-C output: DC 5V=2.4A, 9V=2.22A, 12V=1.67A (20W)
 Wireless output: 15W
 Product size: 103*65*10mm Product weight: 124.5g
 Working temperature: -10°C-50°C




50000mAh

PD 20W




PB790

Capacity: 10000mAh/37Wh Rated capacity: 6300mAh(5V/2A)
 Cell Type: lithium polymer Shell material: Metal+PC
 Type-C input: DC 5V=2.4A, 9V=2.0A (18W)
 Type-C output: DC 5V=2.4A, 9V=2.22A, 12V=1.67A (20W)
 Wireless output: 15W
 Product size: 104*67*15.5mm
 Product weight: 197g
 Working temperature: -10°C-50°C




10000mAh

PD 20W

New

PB791-L

Capacity: 5000mAh/18.25Wh
Rated capacity: 3000mAh(5V/2A)
Shell material: Fireproof ABS+PC
Type-C input: 5V=2.4A, 9V=2A, 12V=1.5A (18W)
For iP output: 5V=2.4A, 9V=2.22A, 12V=1.67A (20W)
Product size: 81*35*28mm
Product weight: 100g
Working temperature: -10 °C-50 °C

50000mAh 20W



New

PB791-T

Capacity: 5000mAh/18.25Wh
Rated capacity: 3000mAh(5V/2A)
Shell material: Fireproof ABS+PC
Type-C input: 5V=2.4A, 9V=2A, 12V=1.5A (18W)
For iP output: 5V=2.4A, 9V=2.22A, 12V=1.67A (20W)
Product size: 81*35*28mm
Product weight: 100g
Working temperature: -10 °C-50 °C

50000mAh 20W



New

PB792

Battery capacity: 10000mAh/37Wh
Rated capacity: 6300mAh(5V/2A)
Core type: Polymer
Housing material: Fireproof ABS+PC+zinc alloy bracket
Type-C output: 5V=3A, 9V=2.22A, 12V=1.67A, (20W)
Type-C input: 5V=2.4A, 9V=2A, 12V=1.5A
Wired maximum power: PD20W
Wireless maximum power: 15W
Product size: 111*72*19.5mm Product weight: 230.5g
Working temperature: -10 °C-50 °C

10000mAh



New

PB793

Capacity: 10000mAh/37Wh
Rated capacity: 6300mAh(5V/2A) Material: ABS+PC
Type-C output: 5V=2A, 9V=2A, 12V=1.5A 18W(Max)
USB output: 4.5V=5A, 5V=4.5A, 5V=3A, 9V=2A, 12V=1.5A 22.5W(Max)
Type-C comes with line input: 4.5V=5A, 5V=4.5A, 5V=3A, 9V=2A, 12V=1.5A 22.5W(Max)
iPH comes with line output: 5V=3A, 9V=2.22A, 12V=1.67A 20W(Max)
Total output: 5V=3A(Max)
Product size: 104.5*63.8*27.6mm Product weight: 247.6g
Working temperature: -10 °C-50 °C

10000mAh 22.5W



New

PB794

Capacity: 20000mAh/3.85V/77Wh
Rated capacity: 12600mAh(5V/2A) Material: ABS+PC
Type-C output: 5V=2A, 9V=2A, 12V=1.5A 18W(Max)
USB output: 4.5V=5A, 5V=4.5A, 5V=3A, 9V=2A, 12V=1.5A 22.5W(Max)
Type-C comes with line input: 4.5V=5A, 5V=4.5A, 5V=3A, 9V=2A, 12V=1.5A 22.5W(Max)
iPH comes with line output: 5V=3A, 9V=2.22A, 12V=1.67A 20W(Max)
Total output: 5V=3A(Max)
Product size: 111.6*69.5*33.6mm Product weight: 335g
Working temperature: -10 °C-50 °C

20000mAh 22.5W



PB798

New

PB796

Battery capacity: 10000mAh/37Wh
Rated capacity: 6000mAh(5V/2A)
Battery material: polymer lithium battery
AC Input: 110-240V 50-60Hz (18W)
Type-C Input: 5V=3A, 9V=2A, (18W)
USB-A Output: 5V=3A, 9V=2A, 10V=2.25A, 12V=1.5A, (22.5W)
Type-C Output: 5V=3A, 9V=2.22A, 12V=1.67A, (20W)
Type-C comes with cable output: 5V=3A, 9V=2.22A, 12V=1.67A, (20W) iP comes with cable Output: 5V=2.4A
Product Size: 120*60*30mm product weight: 254.69g
Operating temperature: -10 °C-50 °C

10000mAh



New

PB798

Battery capacity: 20000mAh
Rated capacity: 12000mAh(5V/2A)
Type-C input/output: 5V=3A, 9V=3A, 12V=3A, 15V=3A, 20V=3.25A(65W MAX)
USB output: 5V=3A, 9V=3A, 10V=2.25A, 12V=3A, 15V=3A, 20V=3A(60W MAX)
Type-C comes with cable input/output: 5V=3A, 9V=3A, 12V=3A, 15V=3A, 20V=3A(60W MAX) iP comes with cable output: 5V=2.4A
Product Size: 110*52.5*49.5mm product weight: 375g
Operating temperature: -10 °C-50 °C

20000mAh





PB7002



PB7003

27000mAh



New

PB799

Capacity: 5000mAh/18.25Wh
Rated capacity: 3000mAh (5V/2A) Material: PC+ABS
Type-C input: 5V=3A, 9V=2A, 18W
Wireless charging output: 5W/7.5W/10W/15W
Type-C output: 5V=3A, 9V=2.22A, 12V=1.67A 20W (Max)
Product size: 76.5*64.5*16.1mm Product weight: 120.37g
Operating temperature: -10°C-50 °C

5000mAh 20W



New

PB7001

Capacity: 10000mAh/37Wh
Rated capacity: 6000mAh(5V/2A) Material: PC+ABS
Type-C input: 5V=3A, 9V=2A, 18W
Wireless charging output: 5W/7.5W/10W/15W
Type-C output: 5V=3A, 9V=2.22A, 12V=1.67A 20W (Max)
Product size: 76.5*64.5*26.4mm Product weight: 195.77g
Operating temperature: -10°C-50 °C

10000mAh 20W



New

PB7002

Battery capacity: 10000mAh/37Wh
Rated capacity: 6300mAh(5V/2A) Core type: Polymer
Housing material: Fireproof ABS+PC+ zinc alloy bracket
Type-C output: 5V=3A, 9V=2.22A, 12V=1.67A, (20W)
Type-C line output: 5V=3A, 9V=2.22A, 12V=1.67A, (20W)
Type-C input: 5V=2.4A, 9V=2A, 12V=1.5A
Wired maximum power: PD20W
Wireless maximum power: 15W
Product size: 111*72*19.5mm Product weight: 232.3g
Working temperature: -10 °C-50 °C

10000mAh



New

PB7003

Battery capacity: 27000mAh/3.6V/97.2Wh
Rated capacity: 16500mAh (5V/2A)
Type-C1/Type-C2 input: 5V=3A, 9V=3A, 12V=3A, 15V=3A, 20V=5A(100W MAX)
USB output: 5V=3A, 9V=3A, 10V=2.25A, 12V=3A, 15V=3A, 20V=3A (60W MAX)
Type-C1+USB output: 100W+45W Type-C2+USB output: 5V=3A
Type-C1+Type-C2 output: 100W+45W
Product Size: 152*54*48mm product weight: 560g
Operating temperature: -10 °C-50 °C

27000mAh



New

PB7004

Battery capacity: 10000mAh/37Wh
Rated capacity: 6000mAh(5V/2A) Material: Fireproof ABS+PC
Type-C input: 5V=2A, 9V=2A, 12V=1.5A
USB output: 4.5V=5A, 5V=4.5A, 5V=3A, 9V=2A, 12V=1.5A (22.5W)
Type-C comes with cable input: 5V=2.4A, 9V=2A, 12V=1.5A
Type-C comes with cable output: 5V=3A, 9V=2.22A, 12V=1.67A(20W)
iP comes with cable Output: 5V=2.4A, 9V=2.22A, 12V=1.67A(20W)
Wired maximum power: PD20W Wireless maximum power: 15W
Product Size: 113*72*22mm product weight: 224.2g
Operating temperature: -10 °C-50 °C

10000mAh



New

PB7005

Battery capacity: 20000mAh/74Wh
Rated capacity: 12000mAh(5V/2A) Material: Fireproof ABS+PC
Type-C input: 5V=2A, 9V=2A, 12V=1.5A
USB output: 4.5V=5A, 5V=4.5A, 5V=3A, 9V=2A, 12V=1.5A (22.5W)
Type-C comes with cable input: 5V=2.4A, 9V=2A, 12V=1.5A
Type-C comes with cable output: 5V=3A, 9V=2.22A, 12V=1.67A(20W)
iP comes with cable Output: 5V=2.4A, 9V=2.22A, 12V=1.67A(20W)
Wired maximum power: PD20W Wireless maximum power: 15W
Product Size: 129*73*30mm product weight: 379.4g
Operating temperature: -10 °C-50 °C

20000mAh





PB7006

Capacity: 10000mAh/38.5Wh
Rated capacity: 5800mAh Material: ABS+PC
Type-C1/C2 input: 5V=3A, 9V=2A (18W MAX)
Type-C1/C2 output: 5V=3A, 9V=2.22A, 12V=1.67A (20W MAX)
Phone wireless output: 15W/10W/7.5W/5W
Headphone wireless output: 3W
IP watch wireless output: 2.5W
Product size: 74.11*117.55*21.5mm Product weight: 179g
Operating temperature: -10°C-50 °C

10000mAh **20W**



PB7007

Capacity: 5000mAh (3.85V/19.25Wh)
Rated capacity: 2800mAh (5V=3A)
Material: lithium polymer battery
Type-C input: 5V=3A, 9V=2A Type-C output: 5V=3A, 9V=2.22A, 12V=1.67A Wireless output: 5W/7.5W/10W/15W
Total output: 5V=3A Energy conversion rate: ≥65%
Product size: 99.5*65.7*9.7mm Product weight: 123.6g
Operating temperature: -10°C-50 °C

5000mAh **15W**



PB7008

Capacity: 10000mAh (3.85V/38.5Wh)
Rated capacity: 5800mAh (5V=3A)
Material: lithium polymer battery
Type-C input: 5V=3A, 9V=2A Type-C output: 5V=3A, 9V=2.22A, 12V=1.67A Wireless output: 5W/7.5W/10W/15W
Total output: 5V=3A Energy conversion rate: ≥70%
Product size: 105*65.7*15.2mm Product weight: 196.39g
Operating temperature: -10°C-50 °C

10000mAh **15W**



PB7009

Cell type: Lithium polymer battery
Capacity: 10000mAh (3.85V/38.5Wh)
Rated capacity: 5800mAh (5V=3A) Material: ABS+PC
Input with A cable: 5V=2A, 9V=2A, 12V=1.5A (18W)
Type-C input: 5V=2.5A, 9V=2A, 12V=1.5A (18W)
Type-C output: 5V=2.4A, 5V=3A, 9V=2.22A, 12V=1.67A (20W)
USB-A output: 5V=4.5A, 5V=3A, 9V=2A, 12V=1.5A (22.5W)
Type-C comes with cable output: 5V=4.5A, 5V=3A, 9V=2A, 12V=1.5A (22.5W) IP comes with cable output: 5V=2.4A
Total output: 5V=3A Product size: 109mm*67.5mm*20.5mm
Product weight: 188.5g Operating temperature: -10 °C-50 °C

10000mAh



PB7010

Cell type: Lithium polymer battery
Capacity: 20000mAh (3.85V/77Wh)
Rated capacity: 11600mAh (5V=3A) Material: ABS+PC
Input with A cable: 5V=2A, 9V=2A, 12V=1.5A (18W)
Type-C input: 5V=2.5A, 9V=2A, 12V=1.5A (18W)
Type-C output: 5V=2.4A, 5V=3A, 9V=2.22A, 12V=1.67A (20W)
USB-A output: 5V=4.5A, 5V=3A, 9V=2A, 12V=1.5A (22.5W)
Type-C comes with cable output: 5V=4.5A, 5V=3A, 9V=2A, 12V=1.5A (22.5W) IP comes with cable output: 5V=2.4A
Total output: 5V=3A Product size: 109mm*67.5mm*34.5mm
Product weight: 327.1g Operating temperature: -10 °C-50 °C

20000mAh



PB7011

Cell type: Lithium polymer battery
Capacity: 10000mAh (3.7V/37Wh)
Rated capacity: 5200mAh (5V=3A) Material: ABS+PC
Type-C input: 5V 2.9A, 9V 2A, 12V 1.5A
Type-C output: 5V 2.4A, 5V 3A, 9V 2.22A, 12V 1.67A
Type-C comes with cable output: 5V 3A, 9V 2A, 12V 1.5A, 10V 2.25A IP comes with cable output: 5V 2.4A
USB-A output: 5V 3A, 9V 2A, 12V 1.5A, 10V 2.25A
Total output: 5V 3A (Max) Product size: 89*60.5*26mm
Product weight: 190g Operating temperature: -10 °C-50 °C

10000mAh





PB7012

Battery type: Lithium polymer battery
Capacity: 10000mAh (3.7V/37Wh)
Rated capacity: 5800mAh (5V=2A) Material: ABS+PC
Type-C input: 5V=2A USB-A1 output: 5V=2A
USB-A2 output: 5V=2A Total output: 5V=2A
Product size: 69.5*145*16mm Product weight: 217.5g
Operating temperature: -10 °C-50 °C

10000mAh



PB7014

Cell type: Lithium polymer battery
Capacity: 10000mAh (3.7V/37Wh)
Rated capacity: 5800mAh (5V=3A) Material: ABS+PC
Type-C input: 5V=2.8A, 9V=2A, 12V=1.5A
Type-C output: 5V=3A, 5V=2.4A, 9V=2.22A, 12V=1.67A
USB-A1 output: 5V=3A, 9V=2A, 12V=1.5A, 10V=2.25A
USB-A2 output: 5V=3A, 9V=2A, 12V=1.5A, 10V=2.25A
Total output: 5V=3A Product size: 69.5*146*16mm
Product weight: 225g Operating temperature: -10 °C-50 °C

10000mAh



PB7013

Battery type: Lithium polymer battery
Capacity: 20000mAh (3.7V/74Wh)
Rated capacity: 11600mAh (5V=2A) Material: ABS+PC
Type-C input: 5V=2A USB-A1 output: 5V=2A
USB-A2 output: 5V=2A Total output: 5V=2A
Product size: 69.5*146*28.5mm Product weight: 393.8g
Operating temperature: -10 °C-50 °C

20000mAh



PB7015

Cell type: Lithium polymer battery
Capacity: 20000mAh (3.7V/74Wh)
Rated capacity: 11600mAh (5V=3A) Material: ABS+PC
Type-C input: 5V=2.8A, 9V=2A, 12V=1.5A
Type-C output: 5V=3A, 5V=2.4A, 9V=2.22A, 12V=1.67A
USB-A1 output: 5V=3A, 9V=2A, 12V=1.5A, 10V=2.25A
USB-A2 output: 5V=3A, 9V=2A, 12V=1.5A, 10V=2.25A
Total output: 5V=3A Product size: 69.5*146*28.5mm
Product weight: 393.8g Operating temperature: -10 °C-50 °C

20000mAh





PB7017

PB7017

Cell type: Lithium polymer battery
Capacity: 10000mAh (3.7V/37Wh)
Rated capacity: 5800mAh (5V=3A) Material: ABS+PC
Type-C input: 5V=2.5A, 9V=2A, 12V=1.5A iP input: 5V=2A, 9V=2A, 12V=1.5A Type-C output: 5V=3A, 5V=2.4A, 9V=2.22A, 12V=1.67A
USB output: 12V=1.5A, 9V=2A, 5V=3A, 5V=4.5A
Type-C cable output: 12V=1.5A, 9V=2A, 5V=3A, 5V=4.5A
iP cable output: 5V=2.4A Total output: 5V=3A (Max)
Energy conversion rate: ≥70% Product size: 147*69*19.4mm
Product weight: 234.5g Operating temperature: -10 °C-50 °C

10000mAh

New



PB7018

Cell type: Lithium polymer battery
Capacity: 20000mAh (3.7V/74Wh)
Rated capacity: 11600mAh (5V=3A) Material: ABS+PC
Type-C input: 5V=2.5A, 9V=2A, 12V=1.5A iP input: 5V=2A, 9V=2A, 12V=1.5A Type-C output: 5V=3A, 5V=2.4A, 9V=2.22A, 12V=1.67A
USB output: 12V=1.5A, 9V=2A, 5V=3A, 5V=4.5A
Type-C cable output: 12V=1.5A, 9V=2A, 5V=3A, 5V=4.5A
iP cable output: 5V=2.4A Total output: 5V=3A (Max)
Energy conversion rate: ≥70% Product size: 147*69*39mm
Product weight: 422.5g Operating temperature: -10 °C-50 °C

20000mAh

New



PB7019

PB7019

Capacity: 10000mAh (3.85V/38.5Wh)
Rated capacity: 5800mAh (5V=3A)
Cell type: lithium polymer battery Casing material: ABS+PC
Type-C input: 5V=2.5A, 9V=2A, 12V=1.5A
Type-C output: 5V=3A, 9V=2.22A, 12V=1.67A (20W Max)
Type-C cable output: 5V=4.5A, 5V=3A, 9V=2A, 12V=1.5A
Total output (Type-C+Type-C line): 5V=3A
Energy conversion rate: ≥70% Product size: 71*66*25mm
Product weight: 171g Working temperature: -10 °C-50 °C

10000mAh

New



VIDVIE

<https://vidvietech.com/>

Foshan
Office: D1-03, Building D, Nanhai New Economic Industry Center,
No. 1 Xianan Road, Guicheng Street, Nanhai District, Foshan City, Guangdong

Shop NO.1 : No. 127, the 1st floor, Guangzhou the thirteen-hongs Culture and Technology Center, Exhibition
Building on the right side of New Asia, No. 37 Xidi Erma Road, Liwan District, Guangzhou

Shenzhen
RmY2-5F-03, No.5 Creative Zone, Yayuan Road, Bantian Street, Longgang District, Shenzhen, China

Shop NO.2 : A46-47, 1/F, Yale Smart Wearable International Market, Block D, Electronic & Technology Building,
Huaqiang North, Shenzhen

Contact Us:

✉ business@vidvietech.com

☎ +86 18565066884

☎ Rain-VIDVIE



VIDVIE® is a registered trademark, owned by Shenzhen Aifeng Chengpin Trading Co., Ltd. Shenzhen Aifeng Chengpin Trading Co., Ltd. has all the right to interpret matters related to this album.
The products displayed in the VIDVIE full-category product catalog are new products as of January 2021. New products on the shelves after January 2021 are not in this catalog. You can consult our sales staff for the latest product information.
If the products shown in this album are revised in the future, please refer to the information provided by the salesperson of our company. This album is for reference only.